SolarEdge Energy Bank 10kWh Battery

For Europe



StorEdge®

Optimized for SolarEdge StorEdge with HD-Wave technology inverters⁽¹⁾

- Maximized system performance, gaining more energy to store and use for on-grid and backup power applications
- Integrates with the complete SolarEdge residential offering, providing a single point of contact for warranty, support, training, and simplified logistics & operations
- DC coupled battery featuring superior overall system efficiency
- Scalable solution for increased power and capacity with multiple SolarEdge inverters and batteries

- Solar, storage, EV charging, and smart devices all monitored and managed by a single app to optimize solar production, consumption and backup* power
- Wireless communication to the inverter, reducing wiring, labor and installation faults
- Simple plug and play installation, with automatic SetApp-based configuration
- Includes multiple safety features for battery protection at all times



^{*} Backup application are subject to local regulation and may require additional components and firmware upgrade

/ SolarEdge Energy Bank10kWh BatteryFor Europe

		BAT-10K1P ⁽²⁾	
OUTPUT			
Usable Energy (100%	depth of discharge)	9700	Wh
Continuous Output Power		5000	W
Peak Output Power in Backup (for 10 seconds)		7500	W
Peak Roundtrip Efficiency		>94.5	%
Warranty ⁽³⁾		10	years
Voltage Range		350-450	Vdc
ADDITIONAL F	FEATURES		
Compatible Inverters		StorEdge Single Phase Inverter with HD-Wave Technology, Single Phase Inverter with HD-Wave Technology ⁽⁴⁾	
Battery per Inverter		Up to 3 ⁽⁵⁾	
Communication Interfaces		Wireless*	
STANDARD CO	OMPLIANCE		
Certification	Cell	IEC 62619	
	Battery	IEC 62619, UN38.3	
Emissions		IEC61000-6-1, IEC61000-6-2, IEC61000-6-3	
INSTALLATION	I SPECIFICATIONS		
Dimensions (W x H x D)		790 x 1179 x 250	mm
Weight		121	kg
Mounting		Floor ⁽⁶⁾ or wall mount ⁽⁷⁾	
Operating Temperature		-10 to +50	°C
Storage Temperature (more than 3 months)		-10 to +30	°C
Storage Temperature (less than 3 months)		-30 to +60	°C
Enclosure Protection		IP55 - indoor and outdoor	
Maximum Altitude		2000	m
Cooling		Natural convection	
Noise at 1m Distance		<25	dBA

^{*} The SolarEdge Energy Bank is designed for use with SolarEdge Energy Net for wireless communication. The inverter might require a matching SolarEdge Energy Net Plug-in (more details below). Using RS485 could reduce the usable energy to 9500Wh.

- (1) Please refer to the SolarEdge Energy Bank battery connections and configuration application note for compatible inverters.
- (2) These specifications apply to part number BAT-10K1PS0B-01.
- (3) For warranty details please refer to the SolarEdge Energy Bank battery Limited Warranty.
- (4) Requires supporting inverter firmware.
- (5) Requires supporting inverter firmware. Installations with multiple SolarEdge Energy Bank batteries require a pair of branch connectors (DC + and DC -) per battery excluding the last battery.
- (6) The floor stand is purchased separately. One floor stand is required per SolarEdge Energy Bank battery. Please refer to the Accessories' PN table below.
- (7) Wall mount installation requires handles that should be purchased separately. Please refer to the Accessories' PN table below.

SolarEdge Energy Bank Battery – Accessories (purchased separately)				
Accessory	PN			
Floor stand	IAC-RBAT-FLRSTD-01			
Handles	IAC-RBAT-HANDLE-01			
Branch connectors set (includes a pair of DC + and DC - connectors) Required for installations with multiple SolarEdge Energy Bank batteries with a single inverter	IAC-RBAT-RWYCBL-01			
SolarEdge Energy Net Plug-in	See SolarEdge Energy Net Plug-in PNs below			

SolarEdge Energy Net Plug-ins			
Inverter Model	Matching SolarEdge Energy Net Plug-in PN		
SolarEdge Energy Net-ready inverter with the following part number format:			
SEBZxx SEBXxx SEBXxx	ENET-xBNP-01		
SetApp-enabled inverter Note: Plugs into the cellular socket Cellular plug-in or ZigBee plug-in cannot be installed in parallel	ENET-xBCL-01		
SetApp-enabled LCD inverter **	ENET-xBRP-01		

^{**} A SolarEdge Energy Net ready Communication Board with LCD is needed.